

# Smartphone

# Smart-Ex® 03

# SMART-EX03-DZ1\*

- Global certificates a common hardware platform
- Android<sup>™</sup> 13 operating system
- Wireless connections such as 5G NR, WWAN, Wi-Fi and Bluetooth®
- Android<sup>™</sup> Enterprise Recommended verified device
- GPS
- NFC technology for wireless applications
- Service contract
- Programmable hardware buttons
- Special buttons for lone worker protection (LWP) applications
- PTCRB and GCF certified
- Dual SIM (eSIM + nano-SIM)
- Google ARCore ready

Smart-Ex 03 DZ1 (DIV 1 and Zone 1/21), Android™, with Camera (optional), 128 GB



Hardware













### **Technical Data**

Qualcomm® Snapdragon QCM6490 and SDR753 platform
Full 3GPP Rel 15 support
8 GByte
Version without camera available.
5 MP
13 MP with LED flash and phase detection autofocus optimized for ECOM scanning solutions
1080p, 720p, 480p (main camera)
128 GByte <sup>1</sup>
Biometric, Accelerometer, Gyrometer, Magnetometer, Barometer, Proximity, Ambient light
Capacitive multitouch
15.24 cm / 6 inch
1080 x 2160
Extreme shock and scratch resistant Gorilla® glass
Can be operated while wearing gloves
Programmable push-to-talk, alarm and multifunction button Power button with fingerprint sensor Volume up/down
Li-lon battery , 4400 mAh
Charging via USB Type C + robust charging pads for charging in docking station (accessory) 3.5 mm audio interface, supporting legacy and standard 3.5mm audio accessories and updated PTT accessories through new, specific audio interface

Mobile standard

<u>_</u>
В
-
0
둤
Ψ
2
2
2
ä
ö
ŭ
77
- 25
=
≥
ಹ
Ē
Φ
团
ш
ω
Q
<u>_</u>
99
Ċ
Ĉί
Ö
8
Φ
⊐
တ္တ
. <u></u>
4
0
(D)
≝
æ
$\Box$
œ
ಷ
ω
Ó
ည်
ñ
ö
≈
Φ
Ħ
~~
_
Φ
as
<u>•</u>
Φ
$\alpha$
_

Technical Data	
2G	GSM: 800 / 850 / 900 / 1800 / 1900 MHz
3G	WCDMA: B1, B2, B4, B5, B8 (850 / 900 / 1700 / 1900 / 2100 MHz)
4G	LTE: B1, B2, B3, B4, B5, B7, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B29, B30, B34, B38, B39, B40, B41, B42, B43, B48, B53, B66, B71
5G	NR: n1, n2, n3, n5, n7, n8, n12, n13, n14, n18, n20, n25, n28, n30, n38, n40, n41, n48 n66, n71, n77, n78, n79
WLAN	6E ready, 802.11a/b/g/n/ac/ax/e/k/r/v, support for Enterprise deployments
Bluetooth	5.2 (BLE supported)
GPS sensor	GPS, GLONASS, Galileo, QZSS, BeiDou
NFC	yes
SIM card	Dual SIM (eSIM + nano-SIM)
Software	
Operating system	Android™ 15 Android™ Enterprise Recommended verified device
SMS/MMS	yes
Cybersecurity	
IT security	
Biometrics	Fingerprint sensor in power button
Updates	Security updates until October 2030 Security update frequency every 90 days Operating system upgrades up to Android™ 15
Certificates	Common Criteria (CC)
Ambient conditions	
Ambient temperature	-20 60 °C (-4 140 °F)
Mechanical specifications	
Degree of protection	IP68 according to EN/IEC 60529 MIL-STD-810H
Mass	400 g
Dimensions	
WxHxD	84 mm x 172 mm x 18 mm / 25 mm
Data for application in connection with haza	rdous areas
ATEX approval	
ATEX certificate	EPS 23 ATEX 1 094 X
ATEX marking	© II 2G Ex ia IIC T4 Gb © II 2D Ex ia IIIC T135 °C Db Ta = -20 °C to +60 °C
International approvals	
IECEx approval	
IECEx certificate	IECEx EPS 23.0021X
IECEx marking	Ex ia IIC T4 Gb Ex ia IIIC T135 °C Db Ta = -20 °C to +60 °C
UKCA approval	
UKCA certificate	EPS23 UKEX 1 095 X
UKCA marking	<ul><li>☑ II 2G Ex ia IIC T4 Gb</li><li>☑ II 2D Ex ia IIIC T135 °C Db</li></ul>
NEC/CEC approval	
NEC/CEC certificate	E115956_PRJ-17072
NEC/CEC marking	U.S. and Canada Class I Division 1 Group ABCD T4 Class II Division 1 Group EFG T4 Class III Division 1  U.S. Class I Zone 1 AEx ia IIC T4 Gb Zone 21 AEx ia IIIC T135°C Db
	Canada Ex ia IIC T4 Gb Ex ia IIIC T135°C Db

# Further approvals Wi-Fi CERTIFIED™ Google ARCore ready PTCRB GCF General information Note Android is a trademark of Google LLC. ¹ no SD Card memory extension Scope of delivery Smart-Ex® 03 Li-lon battery Charger USB cable Screwdriver Documentation

### **Accessories**

Accessories for this product can be found on the internet at www.pepperl-fuchs.com.

